

ADVANTAGE 15W40 PREMIUM PLUS CJ-4 ENGINE OIL

Overview

ADVANTAGE 15W40 PREMIUM PLUS CJ-4 is formulated to meet or exceed the warranty requirements of most manufacturers of diesel and gasoline engines. This oil is formulated to meet the Mack EO-O Premium Plus '07 specification and API CJ-4/SN specification for use in EGR equipped heavy-duty diesel engines in high output service.

Features and Benefits

ADVANTAGE 15W40 PREMIUM PLUS CJ-4 is designed for today's modern ERG equipped engines and older diesel engines. Its superior formula reduces sludge, provides excellent soot control and protects exhaust after treatment devices. ADVANTAGE 15W40 PREMIUM PLUS CJ-4 is highly shear stable, has excellent high temperature stability and low temperature pumpability, in addition to its ability to prohibit sludge and varnish formations while protecting key components from corrosion.

Applications

ADVANTAGE 15W40 PREMIUM PLUS CJ-4 meets the performance requirements of most diesel engine manufacturers such as Caterpillar, Cummins, Detroit Diesel, Ford, Mack, Navistar, and Volvo. It can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, and passenger cars and light trucks with diesel engines, turbo-charged or non turbo-charged and well as gasoline engines.

Recommended For Applications

API CJ-4, CI-4, CI-4 PLUS, CH-4, CF-4 CF/SN • ACEA E9-08 & E7-04 • Caterpillar ECF-3, ECF-2, ECF-1a, TO-2 • Cummins CES 20081, 20077 & 20076 • Detroit Diesel 7SE270, PG PGOS 93K218, 93K214 • International Harvester / Navistar • Mack EO-O Premium Plus, EO-N Premium Plus, EO-M, • Mercedes-Benz 228.31 • MTU MTL 5044 Type 2.1 • Renault VI RLD-3 • Volvo VDS-4, VDS-3, VDS-2

Typicals

PRODUCT CODE	524
CCS, cP (@ -20 °C)	6500
Viscosity, cSt @ 100 °C	15.23
Viscosity, cSt @ 40 °C	114
Viscosity Index	139
Pour Point, °C	-39
Sulfated Ash, Wt. (%)	0.95
Total Base No., (D2896)	8.4
Specific Gravity	0.889
Flash Point, °C	227