Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114 Fax: (215) 244-2118 www.advancedlubes.com



OVERVIEW

ADVANTAGE FULL SYNTHETIC UNIVERSAL CVT FLUID is a superior quality, high performance fluid designed for use in today's metal-belt continuously variable transmissions. Suitable for use in most CVT applications on today's market, ADVANTAGE FULL SYNTHETIC UNIVERSAL CVT FLUID provides superior protection for today's modern vehicles.

FEATURES & BENEFITS

ADVANTAGE FULL SYNTHETIC UNIVERSAL CVT FLUID is specifically designed for both belt and chain driven CVT's and employs the latest additive technology to provide superior protection in all driving conditions. It exhibits superior anti-wear protection, exceptional shear and oxidation stability, and outstanding low-temperature flow characteristics while ensuring optimum component protection.

APPLICATIONS

ADVANTAGE FULL SYNTHETIC UNIVERSAL CVT FLUID is specifically designed to covers most all constantly variable transmission applications. This scientifically formulated product is comprised of premium base stocks and the latest additives to provide maximum protection and long life.

SPECIFICATIONS

Audi/VW TL 52180, TL 52516 (G 052 180, G 052 516) • BMW EZL 799A (8322 0 136 376/8322 0 429 154) • Daihatsu Ammix CVTF-DC, Ammix CVTF-DF • FCA CVTF+4 (05191184AA) • Ford WSS-M2C933-A, MERCON C, WSS-M2C928-A • GM DEX-CVT, CVT* (AC Delco 15234609 [9461], 15250985 [1gal], 15231847 [10cc], 22688912, 19260800, 19299096 [Canada]) • Honda Genuine CVT Fluid / Multi Matic Fluid [HMMF], HCF-2 (08200-9006, 08200-HCF2) • Hyundai/Kia SP CVT-1 • Mazda CVTF 3320 (JWS3320) • Mercedes Benz MB-236.20 (001 989 46 03) • Mitsubishi Dia Queen CVTF J1, J4*, DIAMOND ATF SP III (MZ313973, MZ32018, MZ320200) • Nissan NS-1, NS-2, NS-3* • Subaru e-CVTF, Lineartronic CV-30, Lineatronic CVTF-II, High torque CVTF, i-CVT F, i-CVT FG (SOA427V1600, SOA868V9245, K0425Y0710, SOA427V1660 (qt), SOA427V1610 (gl), SOA868V9245, SOA748V0200) • Suzuki CVT Fluid Green1, Green2, CVTF 3320 • Toyota TC, FE*, WS* (08886-02105, 08888-02505, JWS3324)

*lower viscosity than this product

TYPICAL PROPERTIES

Product Code

Appearance Color Brookfield Vis @ -40°C Viscosity, cSt @ 40°C Viscosity, cSt @ 100°C Viscosity Index

LPROPERTIES	
	547
	B&C
	L2.
	9,570
	33.68
	7.17
	184

ISO 9001:2008 Registered