

Advanced Lubrication Specialties
420 Imperial Court
Bensalem, PA 19020
United States
Tel: (215) 244-2114
Fax: (215) 244-2118
www.advancedlubes.com



ADVANTAGE SYNTHETIC HD 75W140 GEAR OIL

Overview

ADVANTAGE SYNTHETIC HD 75W-140 GEAR OIL is a fully synthetic drivetrain lubricant engineered to meet demanding performance requirements. This product is designed for use in heavy-duty drivetrains that require gear lubricants with relatively high viscosity, excellent load-carrying capability, and where extreme pressures and shock loading are expected.

Features and Benefits

ADVANTAGE SYNTHETIC HD 75W-140 GEAR OIL offers excellent performance over a wide temperature range, helps to protect against thermal breakdown and oxidation, and helps to reduced wear and corrosion while improving shear stability and fuel economy. This is an API GL-5, MT-1, 500,000 mile drain interval capable, limited slip capable fluid suitable for the most demanding commercial applications.

Typicals

PRODUCT CODE	648
SAE Grade	75W-140
Viscosity, cSt @ 40 °C	189
Viscosity, cSt @ 100 °C	28.0
Viscosity Index	175
Flash Point, °C	150
Pour Point, °F	-38
Phosphorus	.100
Sulfur	2.0