Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114 Fax: (215) 244-2118 www.advancedlubes.com



ADVANTAGE ROCK DRILL OILS

OVERVIEW

ADVANTAGE ROCK DRILL OILS are heavily compounded oils designed for the lubrication of pneumatic equipment exposed to excessive moisture or water spray. They are manufactured using premium quality mineral oils and special additive packages designed for heavy-duty rock drill applications. These additive systems employ excellent extreme pressure protection as well as rust and corrosion protection, tackiness, and antifoam properties.

FEATURES & BENEFITS

ADVANTAGE ROCK DRILL OILS provide good adhesion to metal surfaces in the presence of moisture, have excellent extreme-pressure properties and offer exceptional protection against wear, rust, corrosion, and foaming.

APPLICATIONS

ADVANTAGE ROCK DRILL OILS are recommended for and meet the general requirements of major manufactures of jack hammers, rock drills and other makes of pneumatic percussion equipment manufactured by Gardner-Denver, Ingersoll-Rand, and most others.

| TYPICAL PROPERTIES | | | | | | |
|--------------------|--|---|---|---|---|--|
| 669 | 793 | 631 | 640 | 622 | 623 | 624 |
| 32 | 46 | 68 | 100 | 150 | 220 | 320 |
| 10W | 15W | 20W | 30W | 40W | 50W | 60W |
| .864 | .868 | .872 | .876 | .881 | .886 | .890 |
| 31.4 | 47.0 | 67.9 | 106.9 | 152.2 | 218.2 | 333.4 |
| 5.5 | 7.3 | 9.3 | 12.8 | 15.4 | 19.1 | 25.8 |
| 100 | 101 | 99 | 98 | 102 | 95 | 95 |
| 195 | 215 | 220 | 220 | 230 | 235 | 245 |
| -35 | -35 | -25 | -25 | -20 | -15 | -15 |
| 1B | 1B | 1B | 1B | 1B | 1B | 1B |
| >12 | >12 | >12 | >12 | >12 | >12 | >12 |
| 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| .25 | .25 | .25 | .25 | .25 | .25 | .25 |
| PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| | 669 32 10W .864 31.4 5.5 100 195 -35 1B >12 60 .25 | 669 793 32 46 10W 15W .864 .868 31.4 47.0 5.5 7.3 100 101 195 215 -35 -35 1B 1B >12 >12 60 60 .25 .25 | 669 793 631 32 46 68 10W 15W 20W .864 .868 .872 31.4 47.0 67.9 5.5 7.3 9.3 100 101 99 195 215 220 -35 -35 -25 1B 1B 1B >12 >12 >12 60 60 60 .25 .25 .25 | 669 793 631 640 32 46 68 100 10W 15W 20W 30W .864 .868 .872 .876 31.4 47.0 67.9 106.9 5.5 7.3 9.3 12.8 100 101 99 98 195 215 220 220 -35 -35 -25 -25 1B 1B 1B 1B >12 >12 >12 >12 60 60 60 60 60 .25 .25 .25 .25 | 669 793 631 640 622 32 46 68 100 150 10W 15W 20W 30W 40W .864 .868 .872 .876 .881 31.4 47.0 67.9 106.9 152.2 5.5 7.3 9.3 12.8 15.4 100 101 99 98 102 195 215 220 220 230 -35 -35 -25 -25 -20 1B 1B 1B 1B 1B >12 >12 >12 >12 >12 60 60 60 60 60 60 .25 .25 .25 .25 .25 .25 | 669 793 631 640 622 623 32 46 68 100 150 220 10W 15W 20W 30W 40W 50W .864 .868 .872 .876 .881 .886 31.4 47.0 67.9 106.9 152.2 218.2 5.5 7.3 9.3 12.8 15.4 19.1 100 101 99 98 102 95 195 215 220 220 230 235 -35 -35 -25 -25 -20 -15 1B 1B 1B 1B 1B 1B >12 >12 >12 >12 >12 >12 60 60 60 60 60 60 60 .25 .25 .25 .25 .25 .25 .25 |