Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114 Fax: (215) 244-2118 www.advancedlubes.com



# **ADVANTAGE ECONOMY AW SERIES HYDRAULIC OILS**

# **OVERVIEW**

ADVANTAGE ECONOMY AW SERIES HYDRAULIC OILS are highly refined, good quality, general-purpose anti-wear hydraulic oils. Recommended applications include hydraulic systems, mining equipment, moderately loaded gear sets, as well as general purpose lubrication. ADVANTAGE ECONOMY AW SERIES HYDRAULIC OILS provide good wear protection for pumps, motors, and other hydraulic system components. The products have good oxidation resistance, rust and corrosion protection and foam resistance.

#### **FEATURES & BENEFITS**

ADVANTAGE ECONOMY AW SERIES HYDRAULIC OILS have highly refined base oils and latest additive technology that provides solid AW performance for less critical applications. Their excellent price-to-value ratio and very good thermal and oxidation resistance provide the necessary protection to key components.

# **APPLICATIONS**

ADVANTAGE ECONOMY AW SERIES HYDRAULIC OILS are designed for operations such as trash hydraulic systems and other operations where usage and leakage are problems. This lower cost product performs well in many light to medium duty hydraulic systems.

#### **SPECIFICATIONS**

Dennison HF-2 • Vickers I-286-S • Cincinnati P-68, P-69, P-70

### TYPICAL PROPERTIES

| THIOMET HOT EITHES         |       |       |       |
|----------------------------|-------|-------|-------|
| PRODUCT CODES              | 400   | 401   | 403   |
| ISO Grade                  | 32    | 46    | 68    |
| Viscosity Index            | 100   | 100   | 100   |
| Viscosity, cSt @ 40 °C     | 32    | 46    | 68    |
| Pour Point, °C             | -33   | -29   | -24   |
| Flash Point, COC °C        | 215   | 220   | 220   |
| Foam, D892, Seq I/II/III   | 20/0  | 20/0  | 20/0  |
| Copper corrosion, D130     | 1B    | 1B    | 1B    |
| Rust Test, D665            | Pass  | Pass  | Pass  |
| Zinc, %/wt.                | .023  | .023  | .023  |
| Specific Gravity @ 15.6 °C | 31.5  | 30.0  | 28.5  |
| Oxidation Stability        | 3500+ | 3500+ | 3000+ |
| FZG PASS, load test        | 10    | 10    | 10    |