Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114

Fax: (215) 244-2118 www.advancedlubes.com



# **ADVANTAGE FULL SYNTHETIC 15W-40 CK-4**

### **OVERVIEW**

ADVANTAGE FULL SYNTHETIC 15W-40 CK-4 is formulated with all synthetic base stocks and meets or exceeds the latest API diesel engine oil specifications as well as the warranty and performance requirements of most diesel engine manufacturers. This full synthetic product is designed for use in model year 2017 and newer heavy-duty diesel engines in severe, high-output service, as well as being fully backwards compatible to engines requiring any API C service class.

## **FEATURES & BENEFITS**

ADVANTAGE FULL SYNTHETIC 15W-40 CK-4 is specifically designed to provide enhanced performance in heavy duty diesel engines. Increased temperature stability and superior wear protection allow ADVANTAGE FULL SYNTHETIC 15W-40 CK-4 to provide year-round protection in all operating conditions, while its robust additive package has excellent detergency for long engine life and component serviceability. It provides outstanding protection, exceptional oxidation stability and excellent shear stability over any previous API category.

#### **APPLICATIONS**

ADVANTAGE FULL SYNTHETIC 15W-40 CK- 4 is recommended for and can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, and passenger cars and light trucks with diesel engines, turbo-charged or non turbo-charged, where an API CK-4 or earlier C class oil is specified.

#### **SPECIFICATIONS**

API CK-4, CJ-4, CI-4, CI-4, CI-4, PLUS, CH-4/SN • ACEA E9-16, E7-04 • Caterpillar ECF-3, ECF-2, ECF-1a, TO-2 • Cummins CES 20086, 20081, 20077 • Detroit Diesel 93K222, 93K218, 93K214 • Deutz DQC III-10 LA • Ford WSS-M2C171-F1 • JASO DH-2 • Mack EOS-4.5, EO-O Premium Plus, EO-N Premium Plus • MAN 3575 • Mercedes-Benz 228.31 • MTU MTL 5044 Type 2.1 • Renault RLD-4, RLD-3 • Volvo VDS-4.5 VDS-4, VDS-3

#### **TYPICAL PROPERTIES**

Product Code	332
SAE Viscosity Grade	15W-40
CCS, cP (@ -20°C)	5000
Viscosity, cSt @ 100°C	14.8
Viscosity, cSt @ 40°C	111
Viscosity Index	139
Total Base No., (D2896)	10
Zinc, wt%	0.110
Phosphorous, Wt. (%)	0.100
Sulfated Ash, wt.%	1.0