Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114 Fax: (215) 244-2118

Fax: (215) 244-2118 www.advancedlubes.com



ADVANTAGE MODCUT 4575L

OVERVIEW

ADVANTAGE CUT 4575 L is a superior quality cutting oil that is light in color, low in odor, and high in extreme pressure protection.

FEATURES & BENEFITS

ADVANTAGE CUT 4575 L is a worker-friendly fluid that does not contain any sulfur. Light in color, ADVANTAGE CUT 4575 L provides for excellent work piece visibility, while it's low-odor nature allows its use in many facilities and areas where poor ventilation can prohibit the use of some materials. The very low-odor EP system utilized in ADVANTAGE CUT 4575 L extends tool life while providing for wider workplace acceptance.

APPLICATIONS

ADVANTAGE CUT 4575 L is suited for multi-bar and single-bar spindle automatics, drilling, grinding, taping, threading, gear hobbing and broaching. ADVANTAGE CUT 4575 L machines all metals, ferrous, non-ferrous and aluminum with excellent EP properties, heat dissipation, and fluid clarity.

TYPICAL PROPERTIES

PRODUCT CODES	845
Viscosity, cSt @ 100 °C	4.1
Viscosity, cSt @ 40 °C	21.9
Color, ASTM D1500, max.	3.0
Flash Point, °C	195
Pour Point, °C	-18
Lubricity Agent wt.%	8.0