

# ADVANTAGE GL-5 PREMIUM GEAR OILS

## OVERVIEW

ADVANTAGE GL-5 PREMIUM GEAR OILS are multipurpose, extreme pressure gear lubricants which are recommended for hypoid and bevel gear sets used in many front and rear drive differentials. These gear oils are intended for service fill, top-off and refill of hypoid and other drive axles which recommend API GL-5 gear lubricants. Can be used as a top off in limited slip applications but is not a limited slip capable product intended for fill or refill.

## FEATURES & BENEFITS

ADVANTAGE GL-5 PREMIUM GEAR OILS have optimized formulas that prevent gear chatter, exhibit excellent anti-wear and load carrying capabilities, and have outstanding thermal and oxidation stability for long life. The latest additive technology utilized ensure smooth operation under all conditions.

## APPLICATIONS

ADVANTAGE GL-5 PREMIUM GEAR OILS are designed for use in manual transmissions where a GL-5 gear lubricant is recommended. Meet or exceed API GL-5, API MT-1, MIL-PRF-2105E, Ford WSP-M2C197-A & M2C108A, Meritor Automotive 0-76-D, Navistar B-22, PG-2 and Mack GO-J, depending on viscosity.

## SPECIFICATIONS

SAE J-306, J-2360 • API GL-5/MT-1 • MIL-PRF-2105E • Ford WSP-M2C197-A • Meritor Automotive 0-76-D • Navistar B-22, PG-2 • Mack GO-J, (depending on viscosity)

## TYPICAL PROPERTIES

### Product Code

SAE Viscosity Grade

Viscosity, cSt @ 40 °C

Viscosity, cSt @ 100 °C

Viscosity Index

Flash Point, °C

Pour Point, °C

Brookfield Viscosity

150,000 cP @ (°C)

Rust Test

Copper strip corrosion

Foam test (ASTM D 892), foam volume, ml Sequences 1-3

Gravity, ° API

### 601

80W-90

145.7

14.48

97

229

-33

92,500

-26 °C

Pass

1b

TR/0

28.5

### 606

85W-140

451.25

29.55

98

238

-15

110,000

-12 °C

Pass

1b

TR/0

27.5