

## ADVANTAGE GREEN UTH FLUID

### OVERVIEW

**ADVANTAGE GREEN UTH FLUID** is an environmentally friendlier, exceptionally high quality UTH FLUID for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. Formulated with re-refined Group II base oils, this fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

### FEATURES & BENEFITS

**ADVANTAGE GREEN UTH FLUID** has enhanced friction properties that optimize clutch and PTO performance, improve PTO chatter control and has excellent clutch and elastomer compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. **ADVANTAGE GREEN UTH FLUID** has exceptional low temperature, anti-wear, and extreme pressure properties to protect key components and helps promote the ideals of renewable resources.

### APPLICATIONS

**ADVANTAGE GREEN UTH FLUID** is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. This product is suitable for top-up and re-fill of systems. **ADVANTAGE GREEN UTH FLUID** is also used for certain commercial transmission applications requiring **Type A** (Suffix A) or **DEXON™** fluids. Check your manual for your equipment's specific requirements. **Do not use in passenger car automatic transmissions.**

### SPECIFICATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3509, 3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C41-B, M2C48-A/B • International Harvester B-6 Hy-Tran • John Deere J14B/C, J20A/B, J20C (Hy-Gard™), J21A • Kubota UDT/Super UDT/Super UDT<sup>2</sup> Fluids • Massey Ferguson M1110, M1127B, M1129A, M1143, M1141 (Permatran III), M1145 • Minneapolis-Moline 35154, 35202, 35301 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-286-S, 35VQ25 • White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826 (HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F

### TYPICAL PROPERTIES

PRODUCT CODE	402
Viscosity, cSt @ 40°C	59.4
Viscosity, cSt @ 100°C	9.25
Viscosity, cP @ -20°C	4,500
Viscosity, cP @ -40°C	49,000
Viscosity Index	150
Pour Point	-44
Flash Point	432
Sulfated Ash, wt. %	1.48
Zinc, wt. %	.1550