Advanced Lubrication Specialties 420 Imperial Court Bensalem, PA 19020 United States Tel: (215) 244-2114 Fax: (215) 244-2118 www.advancedlubes.com



ADVANTAGE MEHF HYDRAULIC FLUID

OVERVIEW

ADVANTAGE MAXIMUM EFFICIENCY HYDRAULIC FLUID is a highly refined, premium quality semi-synthetic fluid designed to achieve maximum efficiency in off-road or other hydraulic applications where exposure to extreme temperatures may occur.

FEATURES & BENEFITS

ADVANTAGE MAXIMUM EFFICIENCY HYDRAULIC FLUID has been proven to lower fuel and energy consumption over AW hydraulic fluids for the same amount of work. This is down with a boost in power output, better pump flow rates, wider operating temperature capabilities, and a lower total operating compared to regular AW hydraulic fluids.

APPLICATIONS

ADVANTAGE MAXIMUM EFFICIENCY HYDRAULIC FLUID has been specifically designed for severe service applications where high operating temperatures, air entrainment, contamination with water or wear metals and high system pressure could contribute to shortened oil life. This oil is characterized by a high viscosity index, outstanding thermal and oxidative stability, excellent cold temperature properties and high anti-wear content.

TYPICAL PROPERTIES

Product Code	443
Viscosity, cSt @ 40 °C	48
Viscosity, cSt @ 100 °C	10.45
Viscosity Index	185
Oxidation Stability (TOST), hrs.	7000
FZG Pass, Load Stage	10
Flash Point, COC, °C, min.	218
Pour Point, °C, max.	-37
Zinc, %wt.	.1100

The data and OEM specifications listed are accurate to the best of our knowledge. This information listed is typical data and should not be considered a product standard nor a standard upon which acceptance or rejection of delivered product is to be based. It is the owner's responsibility to consult their equipment owner's manual and select the proper lubricant and viscosity grade for a given application. This data is subject to change without notification.