

## ADVANTAGE SAE CD50 SYNTHETIC MANUAL TRANSMISSION FLUID

### OVERVIEW

**ADVANTAGE SAE CD50 SYNTHETIC MANUAL TRANSMISSION FLUID** is a full synthetic, premium quality, SAE 50 heavy duty manual transmission lubricant designed to meet the rigorous demands of extended drain warranty requirements for both on and off highway equipment. It provides outstanding cleanliness, superior oxidation stability and excellent low temperature performance. It is formulated for stability under severe conditions and is suitable for use in transmissions and gear cases where API GL-1 protection is recommended.

### FEATURES & BENEFITS

**ADVANTAGE SAE CD50 SYNTHETIC MANUAL TRANSMISSION FLUID** provides extended drain intervals, all season performance and extended gear life over conventional oils. Its excellent thermal stability and extreme pressure properties allow for high load capacity and high shear stability. **ADVANTAGE SAE CD50 SYNTHETIC MANUAL TRANSMISSION FLUID** has excellent low temperature properties and protects against corrosion, oxidation, and sludge and varnish buildup and is compatible with typical automotive seals and gaskets.

### APPLICATIONS

**ADVANTAGE SAE CD50 SYNTHETIC MANUAL TRANSMISSION FLUID** is designed for heavy-duty manual transmissions requiring API GL-1 and MT-1 performance and where extreme pressure and shock loading are common.

### SPECIFICATIONS

#### TYPICAL PROPERTIES

<b>Product Code</b>	<b>636</b>
SAE Viscosity Grade	50W
Viscosity, cSt @ 40 °C	140
Viscosity, cSt @ 100 °C	17.6
Viscosity Index	146
Flash Point, °C	235
Pour Point °C	-45
Foaming Sequences I, II, III	Pass
Density @ 15°C	.876