

## ADVANTAGE CD 50 SYNTHETIC MANUAL TRANSMISSION FLUID

### OVERVIEW

**ADVANTAGE CD 50 SYNTHETIC MANUAL TRANSMISSION FLUID** is a full synthetic, premium quality, SAE 50 heavy duty manual transmission lubricant designed to meet the demands of extended drain requirements for both on and off highway equipment. It provides outstanding cleanliness, superior oxidation stability and excellent low temperature performance. Formulated for enhanced stability under severe conditions and for use in off-warranty vehicles, it is suitable for transmissions and gear cases where API GL-1 protection is recommended.

### FEATURES & BENEFITS

**ADVANTAGE CD 50 SYNTHETIC MANUAL TRANSMISSION FLUID** provides extended drain intervals of up to 500,000 miles, all season performance and extended gear life over conventional oils. Its excellent thermal stability and extreme pressure properties allow for high load capacity and high shear stability. **ADVANTAGE CD 50 SYNTHETIC MANUAL TRANSMISSION FLUID** has excellent low temperature properties and protects against corrosion, oxidation, and sludge and varnish buildup and is compatible with typical automotive seals and gaskets.

### APPLICATIONS

**ADVANTAGE CD 50 SYNTHETIC MANUAL TRANSMISSION FLUID** is designed for heavy-duty manual transmissions requiring extended life service where extreme pressure and shock loading are common.

### SPECIFICATIONS

**API GL-4/MT-1 • Dana Transmissions • Eaton Transmissions • Mack TO-A • Meritor • Navistar/International**

### TYPICAL PROPERTIES

<b>Product Code</b>	<b>636</b>
SAE Viscosity Grade	50W
Viscosity, cSt @ 40 °C	140
Viscosity, cSt @ 100 °C	17.6
Viscosity Index	146
Flash Point, °C	235
Pour Point °C	-45
Foaming Sequences I, II, III	Pass
Density @ 15°C	.876