

ADVANTAGE FULL SYNTHETIC SP/GF-6A ENGINE OILS

OVERVIEW

ADVANTAGE FULL SYNTHETIC SP/GF-6A PASSENGER CAR ENGINE OILS are specially formulated using synthetic base oils and high-performance additive packages for superior performance benefits over conventional engine oils.

FEATURES & BENEFITS

ADVANTAGE FULL SYNTHETIC SP/GF-6A PASSENGER CAR ENGINE OILS have excellent oxidation stability for long lubricant life, low-temperature protection from cold start wear, low volatility for reduced oil consumption, and increased resistance to viscosity breakdown. They are specifically designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure. **ADVANTAGE FULL SYNTHETIC SP/GF-6A PASSENGER CAR ENGINE OILS** help extend engine life longer than conventional motor oils and enable greater fuel savings and emissions reduction.

APPLICATIONS

ADVANTAGE FULL SYNTHETIC SP/GF-6A PASSENGER CAR ENGINE OILS meet the most demanding lubrication requirements of today's naturally aspirated, turbocharged, direct-injected, gasoline-fueled and flex-fueled engines. These oils are **ILSAC GF-6A** certified, **fully backwards compatible to GF-5** and earlier certifications, have been engineered to meet the latest specifications of Ford Motor Company for protection from LSPI events and are API "Resource Conserving" for improved fuel economy.

SPECIFICATIONS

ALL VISCOSITY GRADES - API SP, SN, SN PLUS, SM, SL, SJ • ILSAC GF-6A, GF-5 • CHRYSLER MS-6395 • GM 6094M

SAE 0W-20 - FORD WSS-M2C962-A1, WSS-M2C947-B1 • HONDA • TOYOTA • MAZDA

SAE 0W-30 - FORD WSS-M2C963-A1, WSS-M2C953-B1, WSS-M2C946-A, (MS-6395 excluded)

SAE 5W-20 - FORD WSS-M2C960-A1, WSS-M2C945-B1

SAE 5W-30 - FORD WSS-M2C961-A1, WSS-M2C946-B1

TYPICAL PROPERTIES

PRODUCT CODES	743	741	744	745	746
SAE Viscosity Grade	0W-20	0W-30	5W-20	5W-30	10W-30
Viscosity, cSt @ 100°C	8.3	11.6	7.9	10.2	10.2
Viscosity, cSt @ 40°C	43.2	65.5	42.1	57.7	63.0
Viscosity, CCS, cP @ °C	5,200 (-35)	6,000 (-35)	5,300 (-35)	5,900 (-35)	6,000 (-30)
Viscosity Index	171	178	162	166	149
Flash Point, COC, °C, min	200	205	205	205	205
Pour Point, °C, max	-45	-45	-45	-45	-40