

## ADVANTAGE CUT 4575 L

### OVERVIEW

**ADVANTAGE CUT 4575 L** is a superior quality cutting oil that is light in color, low in odor, and high in extreme pressure protection.

### FEATURES & BENEFITS

**ADVANTAGE CUT 4575 L** is a worker-friendly fluid that does not contain any sulfur. Light in color, **ADVANTAGE CUT 4575 L** provides for excellent work piece visibility, while it's low-odor nature allows its use in many facilities and areas where poor ventilation can prohibit the use of some materials. The very low-odor EP system utilized in **ADVANTAGE CUT 4575 L** extends tool life while providing for wider workplace acceptance.

### APPLICATIONS

**ADVANTAGE CUT 4575 L** is suited for multi-bar and single-bar spindle automatics, drilling, grinding, tapping, threading, gear hobbing and broaching. **ADVANTAGE CUT 4575 L** machines all metals, ferrous, non-ferrous and aluminum with excellent EP properties, heat dissipation, and fluid clarity.

### TYPICAL PROPERTIES

PRODUCT CODES	845
Viscosity, cSt @ 100 °C	4.1
Viscosity, cSt @ 40 °C	21.9
Color, ASTM D1500, max.	3.0
Flash Point, °C	195
Pour Point, °C	-18
Lubricity Agent wt. %	8.0