

ADVANTAGE EP GEAR OILS

OVERVIEW

ADVANTAGE EP GEAR OILS are premium quality industrial gear lubricants made from highly refined base stocks and modern additive technology. These lubricants are designed to provide excellent performance when load carrying capacity is required due to extreme pressures and shock loading.

FEATURES & BENEFITS

ADVANTAGE EP GEAR OILS offer high thermal stability and utilize a modern Extreme Pressure additive system to maintain clean gear and bearing surfaces, minimize deposits, inhibit rust and corrosion and provide excellent water separation.

APPLICATIONS

ADVANTAGE EP GEAR OILS are designed for industrial enclosed gearing where an AGMA extreme pressure lubricant is specified. Spur, helical, bevel, and worm gear configurations subject to heavy loading and shock loading. Bath, splash, circulating or spray mist lubrication as applicable to the required viscosity grade.

SPECIFICATIONS

AGMA EP 9005-E02 • Cincinnati Lamb P-63 (ISO 68), P-76 (ISO 100), P-77 (ISO 150), P-74 (ISO 220), P-59 (ISO 320), P-35 (ISO 460) • David Brown M, A, E • DIN 51517, Part 3 (CLP) • ISO 12925-1 CKC/CKD • U.S. Steel 224

TYPICAL PROPERTIES

PRODUCT CODES	6163	6293	6253	6173	6213	6183	6833
Product	SUNEP 68	SUNEP 100	SUNEP 150	SUNEP 220	SUNEP 320	SUNEP 460	SUNEP 680
AGMA Number	2EP	3EP	4EP	5EP	6EP	7EP	8EP
Viscosity, cSt @ 40 °C, ASTM D445	68	100	150	220	320	460	680
Viscosity, cSt @ 100 °C ASTM D445	8.8	11.0	15.0	19.3	25.0	28.5	53.0
Viscosity Index ASTM D2270	99	98	98	95	95	95	113
Flash Point, COC, °C, min. ASTM D92	205	230	240	240	240	240	240
Pour Point, ° C ASTM D97	-30	-25	-25	-15	-15	-15	-5
FZG gear test, stages DIN 51354	12	12	12	12	12	12	12
Timken OK Load, lb. ASTM D2782	60	60	60	60	60	60	60
4-Ball Wear Test ASTM D2783 Load-wear index, kgf Weld Point, kgf	250	250	250	250	250	250	250
Steel Pin, Corrosion, ASTM D665 A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion, ASTM D130	1B	1B	1B	1B	1B	1B	1B
Foam Seq. I/II/III, ASTM D892	0/0	0/0	0/0	0/0	0/0	0/0	0/0
Demulsibility, ASTM D2711 Free Water, ml Water in oil, % Emulsion, ml	82.1 0.6 0.0	80.6 0.4 0.0	82.0 0.2 0.0	86.4 0.2 0.0	81.9 0.3 0.0	84.6 0.5 0.0	84.1 0.4 0.0
Demulsibility, ASTM D1401 Emulsion at 82°C, ml	10	12	20	25	25	30	30
Density, ASTM D4052	.874	.881	.892	.891	.891	.887	.892



The data and OEM specifications listed are accurate to the best of our knowledge. This information listed is typical data and should not be considered a product standard nor a standard upon which acceptance or rejection of delivered product is to be based. It is the owner's responsibility to consult their equipment owner's manual and select the proper lubricant and viscosity grade for a given application. This data is subject to change without notification.