



PRODUCT DATA

ADVANTAGE PREMIUM PRODUCTS

*Designed, Marketed, Manufactured and Distributed by Industry Experts
to give you the **ADVANTAGE***

ADVANTAGE FULL SYNTHETIC SQ/GF-7A ENGINE OILS

FEATURES

Specially formulated with Synthetic base oils and high-performance additive components

Optimized for SQ/GF-7A Performance Standards while maintaining all the properties for backwards compatibility to all previous applicable API S and G (ILSAC) Performance Categories

Designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure.

OEM SPECIFICATIONS

ALL VISCOSITY GRADES - API SQ/ILSAC GF-7A CHRYSLER MS-6395
SAE 0W-20 - FORD WSS-M2C972-A1 · HONDA · TOYOTA · MAZDA
SAE 5W-20 - FORD WSS-M2C970-A1
SAE 5W-30 - FORD WSS-M2C971-A1



ENHANCED FUEL ECONOMY



IMPROVED WEAR PROTECTION



ENHANCED ENGINE DURABILITY

SCAN TO



LEARN MORE

Become a Partner,
scan QR code
to learn more

TYPICAL PROPERTIES

PRODUCT CODES	743	744	745	746
SAE Viscosity Grade	0W-20	5W-20	5W-30	10W-30
Viscosity, cSt @ 100° C	8.0	8.2	10.2	10.6
Viscosity, CCS, cP @ ° C max	6,200 (-35)	6,600 (-30)	6,600 (-30)	7,000 (-25)
Pumping Vis, cP max	60,000	60,000	60,000	60,000
Flash Point, COC, °C, min	200	200	200	200
Density @ 15°C	0.87	0.87	0.87	0.87

