



PRODUCT DATA

ADVANTAGE PREMIUM PRODUCTS

*Designed, Marketed, Manufactured and Distributed by Industry Experts
to give you the **ADVANTAGE***

ADVANTAGE SYNTHETIC BLEND SQ/GF-7A ENGINE OILS

FEATURES

Specially formulated with both Synthetic and Group II base oils along with high-performance additive components

Optimized for SQ/GF-7A Performance Standards while maintaining all the properties for backwards compatibility to all previous applicable API and ILSAC Performance Categories (where applicable)

Designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure.

OEM SPECIFICATIONS

SAE 5W-20 - API SQ · GF-7A · CHRYSLER MS-6395 · FORD WSS-M2C970-A1
SAE 5W-30 - API SQ · GF-7A · CHRYSLER MS-6395 · FORD WSS-M2C971-A1
SAE 10W-30 - API SQ · GF-7A · CHRYSLER MS-6395
SAE 10W-40 - API SQ
SAE 20W-50 - API SQ

TYPICAL PROPERTIES

PRODUCT CODES	747	748	749	750	751
SAE Viscosity Grade	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity, cSt @ 100° C	8.9	10.1	11.1	14.2	18.6
Viscosity, CCS, cP @ ° C max	6,600 (-30)	6,600 (-30)	7,000 (-25)	7,000 (-25)	9,500 (-15)
Pumping Vis, cP max	60,000	60,000	60,000	60,000	60,000
Flash Point, COC, °C, min	200	200	200	200	200
Density @ 15 °C	0.87	0.87	0.87	0.88	0.89

ENHANCED FUEL ECONOMY

IMPROVED WEAR PROTECTION

ENHANCED ENGINE DURABILITY

SCAN TO



LEARN MORE

*Become a Partner,
scan QR code
to learn more*

